

Specifications MP523

This page uses Adobe Flash. Click here to install it.

Native Resolution	XGA (1024 x 768)
Projection System	DLP™ technology by Texas Instruments®
Brightness	2000 ANSI lumens
Lamp	180W, 3500/4000 hours (Normal/Economic mode)
Contrast Ratio	2000:1 (Full on/Full off)
Weight	2.4 kg (5.3 lbs)
Noise Level	33/30 dB (Normal/Economic mode)
Resolution Support	VGA(640 x 480) to SXGA(1280 x 1024)
Dimensions	273 x 108 x 215 mm (10.7 x 4.25 x 8.46 inches)
Image Size	30" to 300"
Throw Ratio	1.97 ~ 2.16
Zoom Ratio	Manual Zoom, 1.10:1
Lens	F=2.51 to 2.69, f=21.95 ~ 24.18 mm
Display Color	Full 16.7 million color palette
Aspect Ratio	4:3 Native, 16:9 Selectable
Horizontal Frequency	31-79 kHz
Vertical Scan Rate	50-85 Hz
Input Terminals	PC : Analog RGB: D-sub 15 pin x 1 Component Video: D-sub 15 pin (Shared with Analog RGB connector) S-Video: Mini Din 4 pin x 1 Composite Video: RCA x 1 Audio : Stereo mini jack x 1P
Output Terminals	PC : D-sub (15 pin) X 1 Audio : Stereo mini jack x 1 2 Watt Speaker x 1
Video Compatibility	NTSC, PAL, SECAM
Auto Switching Power Supply	90–240V AC 50–60 Hz
Power Consumption	240W
On-Screen Display Language	English/ French/ German/ Italian/ Spanish/ Russian/ Traditional Chinese/ Simplified Chinese/ Japanese/ Korean/ Swedish/ Dutch/ Turkish/ Czech/ Portuguese / Thai/ Polish
Preset Modes/ Application Modes	PC Input: PC Mode Movie Mode sRGB Mode User Mode White Board Mode Black Board Mode Green Board Mode A/V Input :

	PC Mode
	Movie Mode
	sRGB Mode
	User Mode
Functions	Brilliant Color
	Standby D-Sub Output
	Auto Source (Auto Search)
	Resolution Reminder
	11 Sets of Picture Mode
	Power Saving (Auto off)
	Wall Color Correction
	Blank
	Security Password
	High Altitude Mode
	Freeze
	Lamp Care
Accessories (Standard)	Quick start guide
	Manual CD
	Power Cord
	Remote Control
	Batteries for R/C
	VGA Cable
Accessories (Optional)	Ceiling Mounting Kit
	Presentation Plus
	Spare Lamp Kit
	Soft Carry Case