



VM-42F140S 42" LCD 1080p MONITOR

- 1920 x 1080 High resolution HD Monitor
- 1080Pure™ - all HD inputs connectors deliver a 1080p signal
- Multiple HD input connectors including 3 HDMI™
- Preset and custom video modes for exceptional viewing experience
- Calibrated for optimal video performance



AutoSource™
Automatic source detection and switching



DayBright™
Optimal daytime or nighttime viewing



SpineDesign™
Easy side cable access



Waterfall
Organized cable management

1080Pure™

Offering 1080p resolution out of all HD connectors, including component inputs

Picture Quality

| | |
|------------------------------|--------------------------|
| Screen Size | 42" |
| Native Resolution | 1920 x 1080 |
| Aspect Ratio | 16:10 |
| Brightness (cd/m²) (typical) | 400 |
| Contrast Ratio (min) | 1000:1 |
| Display Colors | 16.7 Million True Colors |
| Viewing Angle | |
| Horizontal | 180° |
| Vertical | 180° |
| Response Time (gray to gray) | 6.5 ms |
| Active Display Area (h x v) | TBD* x TBD* |
| | 42.0" Diagonal |
| Lamp Life (min) | 40,000 Hours |

Compatible Modes

| | |
|--------------------|--------------------------------|
| HDMI | 480i, 480p, 720p, 1080i, 1080p |
| YPbPr | 480i, 480p, 720p, 1080i, 1080p |
| PC | SVGA, XGA, WXGA |
| Optimum Resolution | 1920 x 1080 |

Video Features

| | |
|------------------------------|------------------------|
| Screen Fit Modes | Standard/Fill/Overscan |
| Progressive Scan | Yes |
| 3D Noise Reduction | Yes |
| Inverse 3:2 Pull Down | Yes |
| De-Interlacing | Yes |
| 3D Adaptive Comb Filter | Yes |
| 2D OSD Graphics Engine | Yes |
| Selectable Color Temperature | 3 Presets |
| | 1 User Adjustable |
| Dynamic Contrast | Yes |

Audio

| | |
|-------------|--------------|
| Speaker Qty | 2 |
| Watts | 15 |
| Location | Front Firing |

Convenience Features

| | |
|--------------------------------|-----|
| Autosource™ | Yes |
| SpineDesign™ Cable Management | Yes |
| DayBright™ - High Contrast LCD | Yes |
| for both day and night | |
| Sleep Timer | Yes |

Connectors

| | |
|----------------------|---|
| Video | 1 |
| S-Video In | 1 |
| YPbPr | 2 |
| HDMI + L/R | 3 |
| D-Sub (VGA) In | 1 |
| PC Audio In (mini) | 1 |
| Audio In (Dual RCA) | 5 |
| RS232 Control | 1 |
| Audio Out (Dual RCA) | 1 |
| SPDIF Out (optical) | 1 |
| AC Power In | 1 |

Electrical/Power Consumption

| | |
|------------------------------|-------------------|
| AC Power | 90-240V (50/60Hz) |
| Power Consumption (max) | 180 W |
| Power Consumption (Stand-by) | <3 W |
| Fanless Design | Yes |

Mechanical

| | |
|---------------------------------------|-----------------------|
| Wall Mount | VESA 75 & 100 mm |
| Anti-Tip Over/Theft Deterrent Bracket | Yes |
| Weight with stand | 57.3 lb |
| Dimensions with stand (WxHxD) | 41.5" x 28.0" x 9.0" |
| Weight without stand | 52.0 lb |
| Dimensions without stand (WxHxD) | 41.5" x 25.8" x 4.5" |
| Carton Weight | TBD lb |
| Carton Dimensions (WxHxD) | 45.3" x 31.6" x 10.1" |
| Cabinet Color | Black/Dark Silver |
| UPC Code | 8 82777 XXXXX X |

Certifications and Compatibility

FCC, CE UL, CUL

You can be sure...if it's Westinghouse

